



4 Series 473 Classic



Acqua fredda
Cold water



Per uso quasi frequente
For almost frequent usage



Lancia getto rotante
Rotary lance

TSS[®]
Total Stop
SYSTEM

Caratteristiche Generali - General Features:

- Carrello a 2 ruote completo di manico
- Pompa a 3 pistoni assiali comandati dal piattello oscillante, testa alluminio
- Pistoni in acciaio inox temperato
- Valvola di sicurezza automatica con azzeramento della pressione nella testa pompa
- Sistema di arresto totale dell' idropulitrice a distanza
- Protezione termica del motore
- Filtro acqua ispezionabile
- Lunghezza cavo elettrico 5 m
- Two-wheel trolley with handle
- 3 Axial stainless steel pistons wobble-plate pump with aluminium head
- Tempered stainless steel pistons
- Automatic by-pass valve with pump head pressure discharge
- Remote control for total shut-down of high pressure washer
- Motor thermal protector
- Inspectable water filter
- Electric cable length 5 m

Fornito con - Equipped with:

Pistola
Trigger gun
(41561)



Testina getto regolabile
Adjustable jet nozzle
(43985)



Prolunga lancia
Lance extension
(41563)



Testina getto rotante
Rotary jet nozzle
(41565)



Tubo AP 8 m
HP hose 8 m
(41562)



Mini Patio
(3084354)



Elettropompa con pompa con testa in alluminio e motore con protezione termica

Electric motorpump with aluminium head pump and electric motor with thermal protector



Dati Tecnici / Technical Data

MOD	COD	MAX		It/h		⚡		kg Netto/Net		
		bar	psi	lt/h	gph	kw	rpm		Hz	V
473	14637	160	2300	480	127	2	3400	50-60	220-240~	7,8

Temperatura massima acqua / Max inlet water temperature
50°C 122°F IPX5-S1

Grandezze logistiche / Logistical Data

EAN code	Dimensione scatola Box dimensions (L x W x H) cm	Q.ty Europallet (800x1200 mm)	Container		Camion Full Truck	kg Lordo/Gross
			20 ft	40 ft		
8016287146371	36,5x32,1x58,5	20	440	888	660	11



Battistrada in gomma
Rubber wheels

Filtro acqua ispezionabile
Inspectable water filter